

## MICROWAVE MONOLITHIC INTEGRATED CIRCUIT PACKAGE

### Related Application

This application is based upon prior filed copending provisional application Serial No. 60/231,926 filed September 11, 2000.

### Field of the Invention

This invention relates to microwave monolithic integrated circuits (MMIC), and more particularly, this invention relates to modules having  
5 a microwave monolithic integrated circuit that can be tuned for optimum performance and improved packaging of a MMIC and transceiver module.

### Background of the Invention

10 The recent explosion in wireless telecommunications has increased the demand for high performance millimeter wave radio frequency (RF) modules. One of the major cost and yield drivers for high frequency MMIC modules has been manual tuning to  
15 optimize module performance. The majority of MMIC RF amplifiers are not self biased. Therefore, each amplifier requires gate voltage (Vg) adjustment to tune the amplifier to its nominal operating conditions. This tuning normally occurs after the amplifiers have  
20 been assembled in the module and are connected to the power supply.

In order to have access to the chips in the module, probe stations are required. In addition,

highly skilled operators are necessary to probe these small devices under a microscope. Damage to the chips is very common, even with veteran MMIC technicians.

The needle-like probes used in the tuning cost  
5 thousands of dollars, and usually have a limited life because of wear and tear. It is estimated that it takes 20 to 30 minutes to probe each amplifier.

Many attempts have been made to automate the probing process, and there has been some limited  
10 success. The time and cost, however, involved in designing and using automatic module probing is extensive. In most cases, unique module designs prevent the use of a particular automatic probe station for more than a single module. These drawbacks have  
15 presented a challenge to many companies active in designing and manufacturing RF modules. As a result, high frequency modules are not produced in high volume. In most cases, manufacturers are forced to use expensive equipment and a large staff of qualified  
20 technicians to manufacture large numbers of RF modules.

Chip packaging for MMIC chips also is increasingly important. MMIC radio frequency modules have never been manufactured in high quantity amounts because the MMIC chips are fragile, typically 2 to  
25 about 4 mil thick, and difficult to handle. Air bridges, located over the surface of the chips, make it difficult to pick the chips from the top or exert pressure on the chips.

Special pick-up tools with pick-in-place  
30 equipment have been used to automatically pick-in-place the MMIC chips. These tools are expensive to manufacture and usually different MMIC chips require different tools. This has presented a challenge to different manufacturing companies because most  
35 automatic pick-in-place machines are limited to a

limited number of tools for MMIC chips. In some cases, a manufacturer must use a series of different pick-in-place machines to assemble one radio frequency module. This is inefficient.

5           These MMIC radio frequency modules also are built in low volume amounts because there are usually a high number of MMIC chips, substrates and peripherals that are installed in each module. For example, a typical millimeter wave transceiver would have about 10  
10 to about 15 MMIC chips, 15-20 pieces of substrate, and about 50-60 other peripheral components, such as resistors and capacitors. There is also a requirement that each of the components be connected via wire or ribbon bonds. This has also presented the challenge to  
15 millimeter wave module manufacturing companies.

#### **Summary of the Invention**

The present invention is advantageous and provides a microwave monolithic integrated circuit  
20 (MMIC) package that overcomes the disadvantages of the prior art as noted above. A base plate is matched as to its coefficient of thermal expansion (CTE) with the MMIC. A solder preform is contained on the base plate and is mounted on the solder preform. A chip cover  
25 covers the MMIC and the base plate and chip cover are configured with respective portions that engage each other such that any pads on the MMIC are exposed for wire and ribbon bonding thereto. The base plate and MMIC are secured together by a solder flow process from  
30 the solder preform.

The base plate can be formed from copper tungsten (CuW) or aluminum silicon (AlSi) alloy. It can be about 10 to about 15 mil thick. The chip cover can be formed of plastic and the solder preform can be  
35 formed from a gold-tin alloy. In one aspect of the

the invention, a solder preform is about 1 to about 2 mil thick. The base plate and chip cover can be secured to each other by the solder preform during a solder flow process. The base plate can include side rails that engage the chip cover. The chip cover includes overlapped rails that engage the chip cover.

### **Brief Description of the Drawings**

Other objects, features and advantages of the present invention will become apparent from the detailed description of the invention which follows, when considered in light of the accompanying drawings in which:

FIG. 1 is a schematic circuit diagram of a self-tuned millimeter wave transceiver module of the present invention.

FIG. 2 is an exploded isometric view of a microwave monolithic integrated circuit (MMIC) package of the present invention.

FIG. 2A is a plan view of the MMIC package shown in FIG. 2.

FIG. 2B is a side elevation view of the MMIC package shown in FIG. 2.

FIG. 3 is an exploded isometric view of a multi-layer, thick film, millimeter wave radio frequency transceiver module, and showing the cover, channelization section, multi-layer thick film section, and the bottom plate.

FIG. 4 is an exploded isometric view of the various layers of the thick film section.

FIG. 5 is an exploded isometric view of a transceiver module, and showing the various connections.

**Detailed Description of the Preferred Embodiments**

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

The present invention advantageously eliminates manual amplifier probing and module tuning in MMIC module manufacturing. By using low cost surface mount devices and a microprocessor, the RF module performance can be optimized in real time with no intervention for use in communications, radar, fiber optic, and other RF applications. The advantages include:

1. Optimization of RF MMIC amplifier operation without manual or automatic probing or tuning.
2. A simple low cost solution (< \$1) per amplifier that eliminates module probing and tuning.
3. Self-tuning that requires no die probing or testing.
4. Reduced RF module assembly and test at least by a factor of 5.
5. Chip level self diagnostics.
6. Transmitter gain and output power control without using attenuator chips.
7. Temperature compensation without the use of active attenuator.

8. Reducing/controlling the DC power dissipation as a function of output power, therefore controlling thermal conditions.

9. Testing RF power through the use of a power monitor circuit.

10. Using an embedded microprocessor for continuous real-time optimization of module performance.

11. User optimization of key module performance parameters without circuit design changes.

12. Shutting down the transmitter RF output (sleep mode) for safety without switching off the power supply.

13. Upgrading module performance via module software upgrade, i.e., a customer pays only for needed features.

14. Correcting for parts variation as a function of temperature and frequency using the on board EEPROM to store characteristics data.

FIG. 1 illustrates the low cost circuit used to self bias the MMIC amplifiers. The entire circuit is implemented using low cost commercial off the shelf (COTS) surface mount chips.

As illustrated, a schematic circuit diagram of the self-tuned millimeter wave transceiver module of the present invention is shown. The module includes a radio frequency MMIC chip formed as a module and illustrated by the dashed lines at 12 and a surface mounted digital microcontroller, indicated by the dashed lines at 14.

The MMIC module includes a plurality of amplifiers, as is typical with a MMIC chip, but only illustrates one amplifier 16. The radio frequency signal enters and passes through a filter 18 and into

the amplifier **18** having the normal gate, source and drain. The radio frequency signal passes from the amplifier **16** into other amplifiers **16a** (if present), as known to those skilled in the art. The MMIC chip **12**  
5 can include a large number of amplifiers **16** on one chip, as known to those skilled in the art. The surface mounted digital controller **14** includes a digital potentiometer **20** having a nonvolatile memory circuit. An example of a potentiometer includes a  
10 AD5233 circuit, as known to those skilled in the art. The potentiometer **20** can handle a bias voltage of about -3 volts.

A current sensor **22**, such as a MAX471 with a drain voltage of 3-12 volts, is coupled to ground and  
15 to the amplifier **16** through the drain. The current sensor **22** is connected to a multi-channel sampling, analog/digital circuit **24**, such as an AD7812 circuit, as known to those skilled in the art. Other current sensors connect to other amplifiers (not shown) and  
20 connect to the multi-channel A/D circuit **24**. A temperature sensor **26** is connected to the multi-channel sampling A/D circuit and is operative for measuring the temperature of the MMIC module. A microprocessor **28** is included as part of the surface mounted digital  
25 controller, and operatively connected to an EEPROM **29** and other components, including the multi-channel sampling A/D circuit **24** and the nonvolatile memory digital potentiometer **20**. As shown, the potentiometer **20** is connected to other amplifiers on the MMIC and can  
30 step gate voltage for respective amplifiers and provide individual control.

As also illustrated, the radio frequency signal from the amplifier **16** can pass from passive coupler **30** to a power monitor diode or other detector

circuit **32** connected to ground. This connection from passive coupler **30** can be forwarded to the multi-channel sampling A/D circuit **24**.

The circuit shown in FIG. 1 adjusts  
5 automatically the amplifier gate voltage ( $V_g$ ) until the amplifier **16** reaches its optimum operating condition as measured by the amount of current drawn by the drain ( $I_d$ ), and as measured by the detector circuit **32** at the output of the amplifier (if available). This is  
10 achieved by controlling (through a serial digital interface) the Digital-to-analog (D/A) converter output voltage generated from potentiometer **20**. The D/A converter includes a nonvolatile memory and is currently available with four channels for less than \$3  
15 at the current time.

As the gate voltage is varied, the current sensor **22** provides a voltage output that is proportional to the drain current drawn by the amplifier **16**. The current sensor output is digitized  
20 by the multi-channel serial analog-to-digital converter (A/D) **24** that digitizes the drain current level. The current level word is compared to a pre-stored optimum amplifier drain current level, such as contained in the EEPROM **29**. The gate bias level is adjusted until the  
25 optimum drain current is reached. The detector circuit, which is available either on the MMIC chip or could be added externally, provides a confirmation that the drain current setting is at the optimum level by measuring the output power. The detector output **32** is  
30 compared to a pre-stored value that defines the expected nominal value at the output of the amplifier.

The drain current adjustment, the current sensing and detector output measurements can be implemented in a real-time continuous adjustment mode



by using low cost microprocessor or through a one-time setting that is accomplished during module test. The EEPROM **29** can be used to store preset chip characteristics, such as optimum drain current and  
5 expected output at various stages in the RF circuit.

The current measurement sensor **22** also allows for diagnostics of each amplifier in the circuit. The current measurement circuit will sense any unexpected drop or increase in current draw. By monitoring the  
10 temperature sensor **26**, the microprocessor **28** determines whether a change in current ( $I_d$ ) is caused by a temperature change or malfunction. The status of each amplifier **16** is reported via the digital serial interface.

15 In cases where DC power dissipation is a prime concern because of thermal issues, any amplifiers **16** can be adjusted via the gate bias control such that the amplifiers draw minimal current. A user may select a maximum temperature, and the microprocessor will  
20 maintain the transceiver at or below that temperature by controlling the DC power dissipation in the MMIC chips.

Traditional methods of controlling gain and output power in RF modules has been to use active  
25 attenuators in the transmit chain. This is inefficient because any amplifiers in the chain will dissipate power. By using the digital potentiometer **20**, the gain and output power of each amplifier can be controlled individually or in groups. The present invention  
30 allows the module to have infinite control over gain and output power, without adding active attenuators after each amplifier, thus, reducing cost and eliminating unnecessary DC power dissipation.

RF power sensing can be achieved through the power monitor diode and detector circuit **32** by coupling some of the amplifier output power (15 to 20 dB) into the passive coupler **30**. The output of the coupler is  
5 sensed by a diode **32a**. The output of the diode **32a** is amplified and digitized via the serial A/D converter.

The digital potentiometer **20**, current sensor **22** for each amplifier, and the temperature sensor **26** allows the module to self adjust its gain as a function  
10 of temperature changes. This is accomplished by maintaining the pre-set current draw from each amplifier constant as the module temperature changes. With the present invention, the module gain and output power can be controlled with high precision.

15 A user's ability to program the module gain at any stage in the circuit chain provides the flexibility to trade-off key performance parameters, such as transmitter noise figure (NF) versus intermodulation level (IM), without changing the  
20 circuit design. Real-time individual chip control also allows the user to operate in a desired condition, such as a linear mode for high modulation communications.

It should be understood that the self-optimization technique of the present invention can  
25 also be used on different devices with the MMIC chip, such as a mixer, multipliers, and an attenuator. By pinching off (maximum negative gate bias), all amplifiers in the transmit chain can be highly attenuated (over 50 dB) for safety reasons during  
30 installation. The present invention requires no additional switches or hardware.

The use of the microprocessor **28** and the chip control circuits as explained above allows the module manufacturer to enable only those features that a

customer desires for a particular application. Although the module hardware is identical, the module features will be controlled by software. This allows flexibility of using the same module in many different applications, including wireless point-to-point, point to multi-point or Vsat. Additionally, the use of the microprocessor and a standard interfaces allows programmability and software upgrades (for additional features) of the modules in the field without removing them.

The use of a microcontroller **14** with the associated microprocessor **28** and onboard EEPROM **29** allow for correction and tuning of various functions within the module. The corrections may include, but are not limited to (a) gain variation over temperature, (b) linearization of the power monitor circuit as a function of temperature and frequency, (c) gain equalization as a function of frequency, and (d) power attenuation linearization as a function of frequency and temperature. The use of a microprocessor **28** to control each of the active devices with the RF module, and the use of the EEPROM **29** to store correction factors, allow a high degree of flexibility and enables the module to operate with high accuracy and performance. Module characterization data (gain, power, noise figure) are collected over temperature and frequency during module testing. The correction factors are calculated automatically by a Test Station and stored in the EEPROM **29**. The correction factors are used during normal module operation to provide a desired performance.

The present invention also provides an improved MMIC chip package as shown in FIGS. 2, 2A and 2B. The MMIC package **40** has several advantages.

1. Protection of MMIC chips in coefficient of thermal expansion (CTE) matched packages.

2. Packaging of MMIC chips at very low cost.

5 3. Improved auto pick and placement, direct wire bonding and ribbon bonding, without causing damage to a fragile MMIC.

4. Improved chip performance (isolation) through miniature packaging.

10 5. An RF module housing formed of low cost material, such as aluminum.

FIG. 2 illustrates an exploded isometric view of the package **40**, and showing the MMIC chip **42** and a base plate **44** that is matched as to its coefficient of thermal expansion (CTE) with the MMIC. A solder preform **46** is contained on the base plate **44** and the MMIC is mounted on the solder preform **46**. A chip cover **48** covers the MMIC. As shown, the base plate includes opposing side rails **44a** that extend along a portion of formed edges to leave the end areas open. The chip cover **48** includes opposing and two spaced overlap legs **48a**. The opposing side rails **44a** and overlap legs **48a** are configured such that when the chip cover is placed over the MMIC chip **42**, solder preform **46** and CTE matched base plate **44**, the side rails and overlap legs engage the respective chip cover and base plate, as shown in FIGS. 2A and 2B, to form open areas at the top and side of the corners and to leave exposed any pads **50** on the MMIC for wire and ribbon bonding thereto.

30 The MMIC module production can be similar to surface mount technology by packaging the MMIC chips to facilitate handling of the chips. The base plate **44** is formed of low cost Coefficient of Thermal Expansion (CTE) matched material, such as a copper tungsten

alloy, CuW, or aluminum silicon alloy, ALSi, having a thickness of about 10-15 mil. The cover **48** can be made out of many types of material including plastic. A 1-2 mil solder preform (such as gold tin) is received on the base plate **44**. The cover **48** is shaped in such a manner that it does not cover the chip input and output pads and the DC pads (gate and drain).

The base plate **44**, the cover **48**, the solder preform **46** and the MMIC chips **42** are delivered in waffle packs or similar packaging. These packages are placed on an automatic pick and place (P&P) machine, as known to those skilled in the art. The P&P machine is programmed to pick the base plate and place it in a waffle pack, which can be used at a high temperature for eutectic soldering (such as graphite), using temperature ranges known to those skilled in the art. The P&P machine picks and places the solder preform **46** into the base plate **44**. The MMIC chip is placed on top of the solder preform **46**. The cover is placed over the top of the chip **42**. This process is repeated for every MMIC chip.

It is estimated that the total P&P per chip package would take about 10 seconds. The number of chips that can be packaged in a day using a single P&P machine is well over 8000. The entire waffle pack with the package assembly, including the MMIC chips, is placed in a eutectic solder oven to flow the solder and attach the chip to the base plate and attach the cover to the base plate.

FIGS. 3-5 illustrate an improved radio frequency transceiver module using thick film technology, such as the low temperature cofired ceramic technology known as green tape. More particularly, FIG. 4 illustrates a multilayer substrate board **50**

having different layers of low temperature transfer tape technology (LTTT) sheets, including a DC signals layer **52**, ground layer **54**, embedded capacitors and resistors layer **56**, solder preform layer **58** and top layer **60**.

FIG. 3 illustrates how the different layers in FIG. 4 are combined to form a multilayer thick film substrate board **50** that is received on a base plate **62** with a channelization plate **64** and radio frequency cover **66**. Isolation vias **67** are shown and illustrated. These vias can run across multiple layers down to the ground layer. They can be formed by techniques known to those skilled in the art.

FIG. 5 shows a MMIC transceiver module **70** with the waveguide interface **72** built into the channelization plate **64** and showing the intermediate frequency outputs **74**, local oscillator input **76**, intermediate frequency input **78**, various DC pins **80**, module connectors **82** and external connectors **84** on a CCA.

The present invention improves the MMIC module assembly process by using a low cost multilayer transfer tape thick film board **50** for attaching the MMIC chips **86** and embedding all the peripherals and electrical connections in the multilayer thick film. The present invention offer several benefits.

1. A new use of Low Temperature Transfer Tape Technology (LTTT) multi-layer board for MMW module design and fabrication.
2. Simplification of MMIC module assembly by reducing part count by a factor of five.
3. Reducing peripheral components count by embedding all resistors and capacitors in a multilayer thick film board.

4. Embedding electrical connections in the multi-layer board, thereby reducing the number of wire and ribbon bonds.

5. Using a planar module configuration for ease of assembly, then attaching RF channelization after dies assembly.

6. Improving RF isolation through channelization, compartmentalization and ground vias.

7. Reducing housing cost by using wire-EDM method for channelization, instead of machining.

8. Directly attaching the SMA and K-connectors directly to the multilayer substrate board.

MMIC module production is made similar to surface mount technology by packaging the MMIC modules to allow complete automation of the assembly process. As shown in FIG. 3, the module is made up of the base plate **62**, multilayer alumina substrate **50** formed from the layers, a channelization plate **64** and a cover **66**.

The base plate **62** is a gold plated flat sheet of low cost CTE matched material, such as Cooper Tungsten (CuW), about 1/8 inch thick, in one aspect of the invention. The plate is only cut to size and requires no machining.

The multilayer substrate board **50** is fabricated using the Low Temperature Transfer Tape (LTTT) technology, such as similar to the green tape technology, as well known to those skilled in the art, similar to low temperature cofired ceramic (LTCC) sheets. The LTTT processing closely follows the steps used in well established multi-layer thick film processing, as known to those skilled in the art. The multiple dielectric printing per layer is replaced by a tape lamination step. Both gold and silver conductor systems can be used with LTTT. Interconnects and vias

are formed by techniques known to those skilled in the art.

Although the LTTT process for forming multilayer structures can be applied to a wide variety of dielectric materials and substrate, the material selected for this illustrated aspect of the present invention is a standard 96% alumina substrate. The special formulated conductor materials are screen printed on the alumina substrate, using standard thick film equipment and processing techniques developed for forming conductive interconnects and interlayer vias. The tape sheets are bonded to the substrate using a combination of heat and pressure.

FIG. 4 show an example of the type of layers that can be used to form the alumina board. The number of layers can be as high as 12. The layers could be formed on a base substrate (S), as illustrated, of the type known to those skilled in the art. Each layer is about 2 to about 4 mil thick, and typically about 3 mil thick, and can be used to carry low frequency RF signals, DC signals, ground, or embedded passive components, such as capacitors and resistors. Interconnect or ground vias can be implemented across one or more layers of LTTT film.

This multilayer LTTT alumina substrate is particularly attractive for use with GaAs chip because of its CTE coefficient (7.1). Also, this material has excellent thermal conduction (25-200 W/MK). The MMIC GaAs chips can be attached directly to the substrate using gold tin solder pre-forms or silver epoxy. In cases of thermal concerns, the chips may be attached directly to the base plate using CTE matched shims, or on top of thermal vias that are connected to the bottom surface. These vias can be formed by techniques known to those skilled in the art. For ease of assembly and



wire bonding, the top layer (3 to 4 mil thick) will have cut-outs made exactly to the size of the chips (see Figure 5).

The multilayer substrate costs on the average  
5 about \$1.5 to \$2.5 per layer per square inch. Up to 275 vias per square inch are possible.

The channelization plate **64**, in one aspect of the present invention, is formed of gold plated aluminum, although other materials could be used. The  
10 channels **64a** are cut out using wire EDM methods. The channels **64a** are created to provide the isolation required between the transmit and receiver signals and to generate a cut off to lower frequency signals. The RF cover is also made of gold plated aluminum.

15 FIG. 5 illustrates a MMW transceiver module including the surface mount circuit card assembly (CCA) used to provide the regulator/controller function. The SMA connectors are attached directly to the multilayer substrate. The RF interface waveguide is provided as  
20 part of the channelization plate.

The module shown in FIG. 5 can be assembled by the following technique as one non-limiting example.

1. Pick and place all the MMIC chips on to the multi-layer alumina substrate. The substrate  
25 should have all the low frequency signals connections, DC connections, ground connections, passive devices already embedded in the layers and the solder pre-form.

2. Pick and place the DC connector and the low frequency SMA connectors used for IF and LO  
30 signals.

3. Flow the solder in a vacuum oven to attached the MMIC die and the connectors to the substrate board. Silver epoxy may be used in place of the solder.

4. Wire/wedge bond the MMIC chips to the substrate board.

5. Attach the substrate board to the base plate and the channelization plate using epoxy.

5 6. Install RF cover.

7. Install the regulator/controller surface mount CCA.

This application is related to copending patent applications entitled, "**SELF-TUNED MILLIMETER**  
10 **WAVE RF TRANSCEIVER MODULE,**" and "**THICK FILM MILLIMETER**  
**WAVE TRANSCEIVER MODULE,**" which are filed on the same date and by the same assignee and inventors, the disclosures which are hereby incorporated by reference.

Many modifications and other embodiments of  
15 the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific  
20 embodiments disclosed, and that the modifications and embodiments are intended to be included within the scope of the dependent claims.